



ALLNET

ALL-MC104G-SFP1

Media Converter 10/100/1000BaseT to 1000BaseSX/LX SFP

- 1x 10/100/1000BaseT Ethernet TP Port; 1x 1000BaseSX/LX SFP Slot
- TP Port can support Half/Full-Duplex, Auto-MDI/MDI-X and Auto-Negotiation
- SFP slot can support either Multi or Single Mode SFP (mini Gbic) Modules
- Ethernet 802.3x Flow Control

Art.-Nr.102460

Note: Product specification is subject to change without notice.



Item	Spezifikation
Standards:	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE 802.3z 1000BaseSX/LX IEEE 802.3x Flow Control
Features:	1x 10/100/1000BaseT with RJ-45 Connector 1x 1000BaseSX/LX SFP Module Slot
Data Transfer Rate:	Half/Full-Duplex on TP Port
Transmission Media:	TP:10/100/1000BaseT Cat. 5, 5E, 6 UTP/STP, up to 100 m 1000BaseSX: 62.5/125µm Multi Mode Fiber optic cable, up to 220 m 50/125µm Multi Mode Fiber optic cable, up to 550 m 1000BaseLX: 9/125µm Single Mode Fiber optic cable
Led Indicators:	1x Power on Per Port:(TX): Link, TX ; (FX): Link, RX
Power Requirement:	DC 5V/1A (external Power Supply)
Power Consumption:	3 Watts (Max)
Dimensions:	94 × 71 × 26 mm (L x W x H)
Weight:	280g (only MC)
Environment	Temperature operarting: 0 ~ 50 °C Humidity operating: 10% ~ 90% (non-condensing) Temperature storage: -20 ~ 70 °C Humidity storage: 10% ~ 90% (non-condensing)
Certifications:	CE