



ALLNET

ALL-MC105G-SC-SM

Media Converter 10/100/1000BaseT to 1000BaseLX, SM SC

- 1x 10/100/1000BaseT Ethernet TP Port; 1x 1000BaseLX Ethernet Fiber Port
- TP Port can support Half/Full-Duplex, Auto-MDI/MDI-X and Auto-Negotiation
- Gigabit Fiber Port support Single Mode SC
- Ethernet 802.3x Flow Control

Art.-Nr. 103897

Note: Product specification is subject to change without notice.

www.allnet.de



Item	Specification
Standards:	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE 802.3z 1000BaseLX IEEE 802.3x Flow Control
Features:	1x 10/100/1000BaseT with RJ-45 Connector 1x 1000BaseLX with Fiber Connector SM,SC
Data Transfer Rate:	Half/Full-Duplex on TP
Transmission Media:	TP:10/100/ 1000BaseT Cat. 5, 5E, 6 UTP/STP, up to 100 m 1000BaseLX: 8.3/125µm Single Mode LWL, up to 20 km 8.7/125µm Single Mode LWL, up to 20 km 9/125µm Single Mode LWL, up to 20 km 10/125µm Single Mode LWL, up to 20 km
Led Indicators:	1x Power on Per Port:(TX): Link, TX ; (FX): Link, RX
Power Requirement:	DC 5V/2A
Power Consumption:	3 Watts (Max)
Dimensions:	94 × 71 × 26 mm (L x W x H)
Weight:	230g (only WC)
Environment:	Temperature operarting: 0 ~ 50 °C Humidity operating: 10% ~ 90% (non-condensing) Temperature storage: -20 ~ 70 °C Humidity storage: 10% ~ 90% (non-condensing)
Certifications:	CE