



ALLNET

ALL-CAM2397-LE

IR Mini Bullet Network Camera

- *3MP high resolution*
- *HD real-time video*
- *3D DNR & DWDR & BLC*
- *IR LEDs: up to 30m*
- *IP 66 Outdoor*
- *PoE power supply*
- *Compact design*
- *ONVIF Support*
- *Bracket included*

Article: 114579



The Full HD infrared bullet IP Camera ALL-CAM2397-LE with IP66 case and the sophisticated mechanical design suites well for inhouse- and outdoor installations.

The camera supports 1920 x 1080 Full-HD video and many features of modern network cameras as well.

The ALL-CAM2397-LE is suitable for day & night use and especially for areas where you need high quality recordings. These includes to be monitored properties, public areas, storage facilities and much more.

Technical data	
Camera	
Image Sensor:	1/3" progressive scan CMOS
Min. illumination:	0,07 Lux @F1.2 - 0 Lux mit IR
Shutter time:	1/25s (1/30s) ~ 1/100.000s
Lense:	4mm @ F2.0 (6mm, 12mm optional) 1920 × 1080: Angle of view: 79°(4mm) 2048 × 1536: Angle of view: 70°(4mm)
Day & Night:	IR cut filter with auto switch
Digital Noise Reduction:	3D DNR
Wide Dynamic Range	Digital WDR
Compression	
Video compression:	H.264 / MJPEG
H.264 codec profile:	Main profile
Bit rate:	32 Kbps ~ 16Mbps
Dual stream:	Yes
Image	
Max. Image Resolution:	2048 x 1536
Frame Rate:	50Hz: 20fps (2048 x 1536), 25fps (1920 x 1080), 25fps (1280 x 720) 60Hz: 20fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
Image settings:	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC:	zone configurable



Technical data

Network

Networkstorage:	NAS
Alarm trigger:	Motion detection, tampering alarm
Protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF, PSIA, CGI,ISAPI
General functionalities:	User Authentication, watermark, reset button
Communication interface:	1xRJ45 10M / 100M Ethernet Interface

General

Operating conditions:	-30°C ~ 60°C, humidity 95% (non-condensing)
Power supply:	12 VDC ± 10% , PoE (802.3af)
Power consumption:	Max. 5W (max. 7W with ICR on)
Wheater Proof Rating:	IP66
IR Range:	Up to 30m
Dimension:	604x769x139,3mm (B/H/T), (2.4" × 3.0" × 5.5")
Weight:	500g (1.1 lbs)

Example-Pictures-Outdoor:



Example-Pictures-Indoor:

