



ALLNET

ALL-CAM2397-LEW

IR Mini Bullet Wireless Network Camera

- 3MP high resolution
- HD real-time video
- 3D DNR & DWDR & BLC
- IR LEDs: up to 30m
- IP 66 Outdoor
- PoE power supply
- Compact design
- ONVIF Support
- Bracket included
- Supports Wireless

Article: 126784



The Full HD infrared bullet IP Camera ALL-CAM2397-LEW with IP66 case and the sophisticated mechanical design suites well for inhouse- and outdoor installations.

The camera supports 1920 x 1080 Full-HD video and many features of modern network cameras as well.

The ALL-CAM2397-LEW is suitable for day & night use and especially for areas where you need high quality recordings.

These includes to be monitored properties, public areas, storage facilities and much more. The wireless function gives the cam more flexibility of mounting everywhere.

Technical data	
Camera	
Image Sensor:	1/3" progressive scan CMOS
Min. illumination:	0,07 Lux @F1.2 - 0 Lux mit IR
Shutter time:	1/25s (1/30s) ~ 1/100.000s
Lense:	4mm @ F2.0 (6mm, 12mm optional) 1920 × 1080:Angle of view: 79°(4mm) 2048 × 1536: Angle of view: 70°(4mm)
Day & Night:	IR cut filter with auto switch
Digital Noise Reduction:	3D DNR
Wide Dynamic Range	Digital WDR
Compression	
Video compression:	H.264 / MJPEG
H.264 codec profile:	Main profile
Bit rate:	32 Kbps ~ 16Mbps
Dual stream:	Yes
Image	
Max. Image Resolution:	2048 x 1536
Frame Rate:	50Hz: 20fps (2048 x 1536), 25fps (1920 × 1080), 25fps (1280 x 720) 60Hz: 20fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720)
Image settings:	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC:	zone configurable
Wi-Fi Specification(Only for the products with Wi-Fi module built-in)	
Wireless Standards	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20/40MHz Support
Protocols	„802.11b: CCK, QPSK, BPSK 802.11g/n: OFDM“
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Transmit Output Power	11b: 17±1.5dBm @ 11Mbps 11g: 14±1.5dBm @ 54Mbps 11n: 12.5±1.5dBm
Receive Sensitivity	11b: -90dBm @ 11Mbps (Typical) 11g: -75dBm @ 54Mbps (Typical) 11n: -74dBm (Typical)



Technical data

Network & Storage

Networkstorage:	NAS
Alarm trigger:	Motion detection, tampering alarm
Protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF, PSIA, CGI,ISAPI
General functionalities:	User Authentication, watermark, reset button
Communication interface:	1xRJ45 10M / 100M Ethernet Interface
Storage	SD-Card SDHC 64GB

General

Operating conditions:	-30°C ~ 60°C, humidity 95% (non-condensing)
Power supply:	12 VDC \pm 10% , PoE (802.3af)
Power consumption:	Max. 5W (max. 7W with ICR on)
Wheater Proof Rating:	IP66
IR Range:	Up to 30m
Dimension:	604x769x139,3mm (B/H/T), (2.4" \times 3.0" \times 5.5")

Example-Pictures-Outdoor:



Example-Pictures-Indoor:

