



ALLNET

ALL-CAM2396-LEF

2MP Motorized-Lens Network Bullet Camera IP66

- *Up to 2 megapixel 1920x1080 @ 30fps resolution*
- *Progressive scan CMOS, capture motion video without incised margin*
- *Support dual stream, and the sub-stream for mobile surveillance*
- *High-performance and long service life Infrared LED, Approx. 20 to 30 meters IR range*
- *Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB*
- *Support 120dB wide dynamic range „WDR“*
- *IR cut filter with auto switch*
- *Motorized lens Vario Focal 2,8 - 12mm@F1.4*
- *PoE (Power over Ethernet)*
- *Ingress Protection level: IP66*
- *Working Temperature -30°-60°*

Article: 124631



The Full HD IR Bullet IP Camera ALL-CAM2396-LEF is ideally suited to your IP 66 enclosure and the sophisticated mechanical design for installation in indoor and outdoor applications. It supports a Full HD resolution of 1920 x 1080 pixels and offers many features you'd expect from modern network cameras.

The main focus is thus the focal length and sharpness can be changed on the motorized varifocal lens without handle on the camera The ALL-CAM2396-LEF is suitable for day / night use and is preferred for areas where you need high quality recordings. By Ultra Wide Dynamic Range of 120dB clear night shots are a great strength of the camera. These include to be monitored, inter alia land, public spaces, storage areas and more.

Technical data:	
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0.01Lux @(F1.2,AGC ON), 0 Lux with IR 0.014Lux @(F1.4,AGC ON), 0 Lux with IR focal length 113,0~33,8°
Max. Image Resolution	1920x1080
Lens	2.8 - 12 mm @ F1.4 motorized lens
Day &Night	IR cut filter with auto switch
Lens Mount	diameter 14
Shutter Time	1/3 s to 1/10,000 s
Image	
Max. Resolution	1920 x 1080
Frame Rate	50Hz: 25fps(1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional
Compression Standard	
Video Compression	H.264/ MJPEG
H.264 Compression Type	Main Profile
Video Bit Rate	256 Kbps – 16 Mbps
Dual Stream	Yes



Network	
Network Storage	NAS (Support NFS,SMB/CIFS)
Standard	ONVIF, PSIA, CGI, ISAPI
Alarm Trigger	Intrusion Detection, Line Crossing detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Network Storage	NAS (Support NFS,SMB/CIFS)
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Security	One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet interface
On-board storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Reset Button	Yes
General	
Operating Conditions	-30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10% PoE (802.3af)
Power Consumption	Max. 5.5 W (Max. 7.5 W with IR cut filter on)
Ingress Protection level	IP66
IR Range	20~30 meters
Dimensions	95x105x258,6mm (3,74" × 4x13" x 10,18")
Weight	1,2kg

Dimensions

