



ALLNET

ALL-MC202P-SFP1

Media Converter 10/100/1000BaseTx to MiniGbic Slot

- 1x 10/100/1000BaseT Ethernet TP Port mit IEEE802.3at max. 30W PoE; 1x 1000BaseSX/LX SFP Slot
- TP Port support Half/Full-Duplex, Auto-MDI/MDI-X and Auto-Negotiation
- SFP slot can support either Multi or Single Mode SFP (mini Gbic) Modules
- Ethernet 802.3x Flow Control
- **Industrial-Temp-Range -20° to +60°C**

Art.-Nr.124821

Note: Product specification is subject to change without notice.

www.allnet.de



Item	Spezifikation
Standards:	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE 802.3z 1000BaseSX/LX IEEE 802.3x Flow Control
Features:	1x 10/100/1000BaseT with RJ-45 Connector 1x 1000BaseSX/LX SFP Module Slot
PoE:	IEEE802.3at/af compatible max. 65W Power Supply
Data Transfer Rate:	Half/Full-Duplex on TP Port
Transmission Media:	TP: 10/100/1000BaseT Cat. 5, 5E, 6 UTP/STP, up to 100 m 1000BaseSX: 62.5/125µm Multi Mode LWL, up to 220 m 50/125µm Multi Mode LWL, up to 550 m 1000BaseLX: 9/125µm Single Mode LWL
Led Indicators:	PWR, SYS, Link/ACT, PoE
Power Requirement:	DC 52V/1, 25A external power supply
Power Consumption:	3 watts (Max)
Dimensions:	185 × 134 × 35 mm (L x B x H)
Weight:	280g (only MC)
Environment	Temperature operarting: -20 ~ +60 °C Humidity storage: 10% ~ 90% (non-condensing)
Certifications:	CE
added Accessories	Power Supply