Full HD Multi-Res Compact IP Dome Camera Quick Guide

The quick guide is for quick installing and connecting the Full HD Multi-Res Compact IP Dome Camera. For details, please refer to the camera's user manual.

Ethernet Connection

Please follow the instructions below to complete IP Dome Camera installation.

Indoor Camera

Connect the one end of the PoE cable to the Ethernet port on the camera, and the other end to Power Sourcing Equipment (PSE) like hubs or routers.



NOTE: Check the status of the link indicator and activity indicator LEDs; if the LEDs are unlit, please check LAN connection.

Green Link Light indicates good network connection. Orange Activity Light flashes for network activity indication.

Rugged Camera

For the Rugged IP Dome Camera, connect its Ethernet cable to a M12/RJ-45 waterproof switch. Please refer to the IP Dome Camera's user manual for further details.

Before Login to the IP Dome Camera

A client program will be automatically installed on your PC when connecting to the IP Dome Camera. Before accessing to the IP Dome Camera, please ensure downloading the ActiveX control is allowed by either changing the ActiveX controls and plug-ins or setting Internet's security level to default. For further details, please refer to the IP Dome Camera's user manual.

ActiveX Controls and Plug-ins Settings	Internet Security Level
Step 1: Start the Internet Explorer (IE).	Step 1: Start the IE.
Step 2: Select <tools> from the main menu of the</tools>	Step 2: Select < Tools> from the main menu of the
browser. Then Click <internet options="">.</internet>	browser. Then Click <internet options="">.</internet>
Step 3: Click the <security> tab and select "Internet",</security>	Step 3: Click the <security> tab and select "Internet."</security>
and click <custom level=""> to change ActiveX</custom>	Step 4: Down the page, press "Default Level" and click
settings.	"OK" to confirm the setting. Close the browser
Step 4: Set "ActiveX controls and plug-ins" items to	window, and open a new one later for
<prompt> or <enable>.</enable></prompt>	accessing the IP Dome Camera



IP Dome Camera Login

The IP Dome Camera's default IP address is getting from DHCP. Therefore please use the Device Search program (on CD) or another IP-Scanner to find your Camera.

Login ID & Password

- Key in the IP Dome Camera's IP address in the URL bar of the Web browser window and press "Enter."
- Enter the default user name (Admin) and password (1234) in the prompt request dialogue. Note that user name is case sensitive.

Install the ActiveX control

- After connecting to the IP Dome Camera, the request for installing the ActiveX control will appear just below the URL bar.
- Right Click on the information bar, and press "Install ActiveX Control..." to permit ActiveX control installation.

😋 🕢 👻 🙋 http://192.168.0.250				• •	X Live Search	P -
File Edit View Favorites Tools Help						
🖌 🕸 🌈 network HD Camera]			• 🔝 • 🖶 • 🔂 Page • 1	💮 Tools 🔻
) This site might require the following ActiveX control: 'Mega	pixel IP Camera \	/iewer' from 'DYN	ACOLOR,	Install ActiveX Control What's the Risk?		
Megapixel	Cuatom	Straamina	Comor			

Connections	Programs	Advanced
y settings.	0	
d sites Re	stricted sites	
ites,	Sit	es
s, click Custon ded settings, c	n level. click Default	level.
s, click Custon Jed settings, c om level	n level. Lick Default Default	level,
s, click Custon Jed settings, c om level Reset all zone	n level. click Default Default is to defaul	level. level

• Press "Finish" when DC Viewer installation is complete.



Full HD Multi-Res Compact IP Dome Camera **Quick Guide**

Ver1.2

Browser-based Viewer

The main page of the IP Camera user interface is as shown below. Please note that the function buttons will vary depending on the camera model.



00P5NV102ZXSEA2