

Quick Install Guide



ALL-SG8308PM

To access the web interface of the ALL-SG8308PM, please start your browser.

This are the factory default settings:

IP-Adresse: 192.168.2.1

Password: admin

Use this configuration to access the webinterface for your PC:
IP: 192.168.2.X (X = 2-254) Subnetmask 255.225.225.0 .

Next start your browser and type **192.168.2.1** into the browser address bar. Apply with enter.

Now you can log onto the webinterface with password **admin**.

A screenshot of a web interface for logging in. It features a dark gray background with a lighter gray border. At the top, the word "LOGIN" is displayed in white capital letters. Below it, the label "Password:" is followed by a white rectangular input field. To the right of the input field is a gray button with the word "Apply" in white text.

RESET TO FACTORY DEFAULT:

Press the reset button for about 30 seconds.

Then the device will restart with factory default settings.



CE-Declaration of Conformity

For the following equipment:

Smart Managed 8 Port Gigabit Switch

ALL-SG8308PM



The safety advice in the documentation accompanying the products shall be obeyed. The conformity to the above directive is indicated by the CE sign on the device.

The ALLNET ALL-SG8308PM conforms to the Council Directives of 1995/5/EC.

This equipment meets the following conformance standards:

EN55022:2010: Class A

IEC61000-3-2: 2005 + A1: 2008 + A2: 2009

IEC61000-3-3: 2008

EN55024: 2010

IEC61000-4-2: 2008

IEC61000-4-3: 2006 + A1: 2007 + A2: 2010

IEC61000-4-4: 2004 + A1: 2010

IEC61000-4-5: 2005

IEC61000-4-6: 2008

IEC61000-4-8: 2009

IEC61000-4-11: 2004

This equipment is intended to be operated in all countries.

This declaration is made by
ALLNET GmbH Computersysteme
Maistraße 2
82110 Germering
Germany

Germering, 09.03.2015



Wolfgang Marcus Bauer
CEO